

BSP THREADED TYPE "Y" STRAINER

PN 16

F 1141

Ref. : F 1141.pas

Rev. : F

Date : 10/12/2012



PA Ventil AB

GO WITH OUR FLOW

APPLICATION

- General use : Filtering for all kind of fluids.

GENERAL CHARACTERISTICS

- From DN 1/2" to DN 4".
- Brass "Y" body, brass bonnet.
- Dismountable stainless steel strainer.
- PN16.

CONSTRUCTION

4	1	Bonnet	Brass	DIN : CUZn40Pb2 ASTM : B16 C37700 BS : 12164 CZ122
3	1	Gasket	PTFE	
2	1	Strainer	Stainless steel 304	DIN : G-X6CrNi18 9 ASTM : Grade CF8 BS : 304 C15
1	1	Body	Brass	DIN : CUZn40Pb2 ASTM : B16 C37700 BS : 12164 CZ122
Pos.	Qty.	Description	Material	



DIMENSIONS

DN	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
L	56	68,5	79,5	92,5	106,5	126	151	172	219
H	39,5	45	54	61,5	70,8	88	107	120	161
Weight (kg)	0,12	0,2	0,3	0,58	0,78	1,4	2,5	3,7	6,6
Mesh (mm)	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8

WORKING CONDITIONS

PS max : 16 bar
T max: +120°C

Test procedures are established according to standard EN 12266-1, DIN 3230, BS 6755 and ISO 5208 :
- Body: 24 bar

STANDARDS

BSP threaded according to standard ISO 228-1.

