

SCREEN FOR FLANGED TYPE STRAINER F 3240 EP PN 16 F 3240TAMIS-IN

Ref. : F3240TAMIS-IN

Rev. : Initial

Date : 08/01/2014



PA Ventil AB

GO WITH OUR FLOW

APPLICATION

For all types of fluids.

GENERAL CHARACTERISTICS

Stainless steel screen.
Rolled, welded construction.

CONSTRUCTION

Stainless steel 304 body

DIMENSIONS

DN		L	Ø D	K	E	Bore diameters	Weight (kg)
mm	inch						
15	1/2"	69	17	10	0.6	1	0.02
20	3/4"	77.5	23				0.03
25	1	97	27				0.045
32	1 1/4	116.5	35				0.075
40	1 1/2	91.2	42				0.1
50	2"	105.2	52			1.3	0.13
65	2 1/2	127.2	67				0.18
80	3"	140.7	82				0.25
100	4"	180.2	102				0.34
125	5"	215.7	127				0.48
150	6"	234.2	152	15	0.8	1.6	0.63
200	8"	296.5	202				1.1
250	10"	393.5	252				1.76
300	12"	426	302			2.5	
350	14"	612	362			3.9	
400	16"	689	410			5	

WORKING CONDITIONS

Maximum working pressure: 16 bar (TS max + 140°C)

Test pressure according to EN 12266-1,
DIN 3230, BS 5154 and ISO 5208

STANDARDS

For use only with flanged type PN16 strainer F3240EP

